

SOPREMA ALSAN RS FINISH
TOP COAT PIGMENTED OR
SMOOTH FINISH (OPTIONAL)

SOPREMA ALSAN RS MEMBRANE

4" (10cm) WIDE SOPREMA
ALSAN RS MEMBRANE
STRIP OR TAPE APPLIED
OVER SOPREMA ALSAN RS
PRIMER (IF REQUIRED) AT
ALL BOARD JOINTS OR
VOIDS

NEW OR EXISTING
VAPOR BARRIER
MEMBRANE

SOPREMA ALSAN RS
PRIMER APPLIED TO
SUBSTRATE (IF REQUIRED)


ACCEPTABLE RECOVERY
BOARD OR OVERLAYMENT
SECURED TO SUBSTRATE.

MIN. 1" SOPREMA RIGID BOARD
INSULATION SECURELY ATTACHED
TO THE SUBSTRATE AS PER
SOPREMA REQUIREMENTS.

ACCEPTABLE SUBSTRATE

NOTES:

1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.

		310 QUADRAL DRIVE	
		WADSWORTH, OHIO 44281 (330) 334-0066	
TITLE RECOVERY BOARD WATERPROOFING ASSEMBLY			
SCALE NONE	DWN TM	CHK MT	APPROVAL DATE 9/24/12
DRAWING NUMBER A-12a-RS			REV 0

** USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.