

SOPREMA ALSAN RS FINISH TOP COAT (EMBEDMENT COAT)

SOPREMA ALSAN RS FINISH COLOR OR CLEAR COAT (OPTIONAL SEALCOAT)

SOPREMA ALSAN RS PRIMER APPLIED TO ACCEPTABLE RECOVERY BOARD

ACCEPTABLE MINERAL AGGREGATE SURFACING BROADCAST INTO WET SOPREMA ALSAN RS TOP COAT.

SOPREMA ALSAN RS MEMBRANE


ACCEPTABLE RIGID INSULATION HOT MOPPED, COLD APPLIED OR MECHANICALLY FASTENED.

1/2" MIN. APPROVED RECOVERY BOARD MECH. FASTENED TO DECK

1/2" MIN. CDX SHEATHING SCREWED TO EXISTING T&G PLANK OR ROOF FRAMING.

NOTES:

1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.

		310 QUADRAL DRIVE WADSWORTH, OHIO 44281 (330) 334-0066	
		TITLE INSULATED WATERPROOFING ASSEMBLY OVER WOOD FRAME CONSTRUCTION	
SCALE	DWN	CHK	APPROVAL DATE
NONE	DMT	MT	3/20/07
DRAWING NUMBER			REV
A-8-RS			0

** USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.