


NOTES:

1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPROVED DETAILS AND ALSAN RS FLASHING APPLICATION AND COVERAGE DIRECTIONS.
2. ALSAN RS FLASHING 20 WET MILS COVERAGE RATE IS 1.25 GALS/100FT. ALL COVERAGE RATES ARE APPROXIMATE, THEORETICAL AND DO NOT ACCOUNT FOR WASTE, SPILLAGE, IRREGULAR SURFACES AND APPLICATION TECHNIQUES THAT CAN ALSO VARY WITH INSTALLER. RATES MAY ALSO VARY DEPENDING UPON MATERIAL AND AMBIENT TEMPERATURE(S), SURFACE FINISH AND POROSITY OF THE SUBSTRATE.
3. FLASHING MAY BE TERMINATED AT GRADE
4. A BASE LAYER OF COLPHENE FLAM 180 MAY BE USED

		310 QUADRAL DRIVE	
		WADSWORTH, OHIO 44281 (330) 334-0066	
TITLE ANTIROCK UPSTAND DETAIL (BRIDGES, PARKING DECKS)			
SCALE	NONE	DWN TM	CHK JP
DRAWING NUMBER		APPROVAL DATE	
ANT03		06/30/10	
			REV 0

** USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.