

EXISTING EXTERIOR WINDOW PANEL AND FRAME.

(1) PLY SOPREMA ALSAN RS MEMBRANE FLASHING EXTEND 4" (10cm) MIN. HORIZONTALLY ONTO PREPARED & PRIMED SUBSTRATE.

CUT-IN REGLET 1" MIN. DEEP, APPLY APPROVED CAULKING AS REQUIRED.

4" MIN. SOPREMA ALSAN RS TOP COAT PIGMENTED FINISH AS SPECIFIED
SOPREMA ALSAN RS FIELD MEMBRANE

ACCEPTABLE CONCRETE SLAB

4" MIN. (1) PLY SOPREMA ALSAN RS MEMBRANE FLASHING EXTEND 8" (20cm) MIN. HORIZONTALLY ONTO MODIFIED BITUMEN ROOF MEMBRANE.

PREPARE, LEVEL & PATCH SUBSTRATE W/ ALSAN RS PASTE OR ACCEPTABLE PATCHING MORTAR PRIOR TO APPLICATION OF SOPREMA ALSAN RS PRIMER & MEMBRANE (TYP.)


ACCEPTABLE FILLER MATERIAL AS REQ. INSTALLED OVER SOPREMA DRAINAGE MAT

SOPREMA ALSAN RS BOND/WEARING COAT W/ BROADCAST QUARTZ SILICA APPLIED OVER MEMBRANE

8" MIN. SOPREMA APPROVED DRAINAGE MAT

SOPREMA BUR OR GRANULATED CAP SHEET MEMBRANE

NOTES:
1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.

		310 QUADRAL DRIVE WADSWORTH, OHIO 44281 (330) 334-0066		
		TITLE PLAZA / DECK WATERPROOFING		
SCALE	NONE	DWN DMT	CHK MT	APPROVAL DATE 5/30/07
DRAWING NUMBER B-20-RS				REV 0

** USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.