

METAL DRIP EDGE—ABRADE & CLEAN FLANGE W/SOPREMA ALSAN RS MEMBRANE CLEANER & SET IN BED OF ACCEPTABLE SEALER.

SOPREMA ALSAN RS MEMBRANE FLASHING—EXTEND FULL WIDTH OF FLANGE & 4" (10cm) MIN. ONTO PREPARED & PRIMED SUBSTRATE.

FASTENERS 4" (10cm) O.C., STAGGERED 1".

1/4" HEM

4" ALSAN RS MEMBRANE REINFORCEMENT STRIP, APPLIED AT ALL JOINTS AND VOIDS

2" MIN (5cm)

4" (10cm)


ALSAN RS FIELD MEMBRANE

THERMAL INSULATION AND COVERBOARD APPLIED TO THE DECK AS SPECIFIED OR REQUIRED

WOOD NAILERS INSTALLED WITH BOND BREAKERS AND FASTENED AS SPECIFIED OR REQUIRED BY CODE OR INDUSTRY STANDARDS TO RESIST DESIGN LOADS AND CORROSION OF STEEL DECKING, FASTENERS AND METAL EDGING.

GUTTER & SUPPORT STRAPS BY OTHERS. EXPOSED FASTENERS MUST BE FASTENED ALONG VERTICAL FACE OF DRIP EDGE & USE ACCEPTABLE SEALING WASHERS.

NOTES:
1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.

		310 QUADRAL DRIVE	
		WADSWORTH, OHIO 44281 (330) 334-0066	
TITLE INSULATED GUTTER EDGE FLASHING			
SCALE NONE	DWN TM	CHK MT	APPROVAL DATE 3/11/13
DRAWING NUMBER EI-3-RS			REV 0

** USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.