



SOPREMA APPROVED SEALANT

SOPRA-FLASH UN MECH.  
FASTENED EVERY 12" O.C.  
WITH TERM. BAR AND  
APPROVED FASTENERS  
(REF NOTE # 4 ON HRW 402)

INSTALL APPROVED SEALANT  
WITH CONCAVE FINISH TO  
FACILITATE WATER RUN-OFF

SUPPORTED/RESTRAINED WALL  
OR CURB SUBSTRATE SURFACE  
PREPARED AS REQUIRED BY  
SOPREMA TO RECEIVE  
FLASHING MEMBRANE.

REGLET MOUNTED METAL  
COUNTERFLASHING

COLPHENE 180 GR OR APPROVED  
ALTERNATE. EMBED IN COLPHENE H  
AND EXTEND OUT ONTO FIELD 4" MIN.

APPROVED COLPHENE H  
215 mils WATERPROOFING  
SYSTEM

CONCRETE DECK (PRIME AS REQUIRED)

SOPRA-FLASH UN

COLPHENE H

(GRANULATED) CAP

NOTES:

1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.

		310 QUADRAL DRIVE WADSWORTH, OHIO 44281 (330) 334-0066	
TITLE REGLET MOUNTED COUNTER FLASHING			
SCALE	NONE	DWN TM	CHK JP
DRAWING NUMBER			APPROVAL DATE
HRW-405B			11/24/09
			REV 0

\*\* USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.