

RAIL POST TUBE SET DOWN OVER STEEL POST. ENSURE TIGHT AND SECURE FIT.

ASSURE FULL SATURATION OF FLEECE & CONTACT W/ SUBSTRATE.

EXTEND SURFACE PREP MAX. 1/8" BEYOND LINE OF SOPREMA ALSAN RS FLASHING & COVER W/ SOPREMA ALSAN RS RESIN

STEEL BASE FLANGE PLATE SECURELY MOUNTED AND FASTENED TO SUBSTRATE.

ASSURE TIGHT FIT AND FULL SECUREMENT OF RAIL POST INSERT SLIP-ON TUBE.

SOPREMA ALSAN RS FIELD MEMBRANE

SOPREMA ALSAN RS MEMBRANE COLLAR CUT INSIDE DIA. SAME SIZE AS PIPE DIAMETER


2" min. 3cm  
3" min. 8cm  
1" min. 5cm

3" min. 8cm  
2" min. 3cm  
1" min. 5cm

OPTIONAL CANT FORMED W/ ALSAN RS PASTE OR OTHER APPROVED PATCHING MORTAR MATERIAL.

NOTES:

1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.

		310 QUADRAL DRIVE WADSWORTH, OHIO 44281 (330) 334-0066	
		TITLE RAIL POST BRACKET	
SCALE	DWN	CHK	APPROVAL DATE
NONE	DMT	MT	10/11/07
DRAWING NUMBER			REV
P-1b-RS			0

\*\* USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.