

AS REQUIRED (VARIES)


4" (10cm) MIN.

(1) PLY SOPREMA ALSAN RS MEMBRANE FLASHING EXTENDED 4" MIN. HORIZONTALLY ONTO PREPARED & PRIMED SUBSTRATE

BOTTOM OUTSIDE CORNER—SEE TYPICAL SOPREMA ALSAN RS OUTSIDE CORNER DETAIL.

SOPREMA ALSAN RS FIELD MEMBRANE

- NOTES:
1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.

|   |     |                       |               |
|---|-----|-----------------------|---------------|
|  |     | 310 QUADRAL DRIVE     |               |
|   |     | WADSWORTH, OHIO 44281 |               |
|   |     | (330) 334-0066        |               |
| TITLE   |     |                       |               |
| CURB/PAD ENCAPSULATION DETAIL   |     |                       |               |
| SCALE   | DWN | CHK                   | APPROVAL DATE |
| NONE  | DMT | MT                    | 3/20/07       |
| DRAWING NUMBER  |     |                       | REV           |
| P-5-RS  |     |                       | 0             |

\*\* USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.