


SUPPORTED/RESTRAINED WALL OR CURB SUBSTRATE SURFACE PREPARED AS REQUIRED BY SOPREMA TO RECEIVE R-NOVA + MINIMUM 2" HEIGHT.

WOOD NAILERS INSTALLED WITH BOND BREAKERS AND FASTENED AS SPECIFIED OR REQUIRED BY CODE OR INDUSTRY STANDARDS TO RESIST DESIGN LOADS AND CORROSION OF STEEL DECKING, FASTENERS AND METAL EDGING.

NOTES:

1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPROVED DETAILS AND R-NOVA + APPLICATION AND COVERAGE DIRECTIONS.
2. R-NOVA + FIELD ASSEMBLY NOT SHOWN FOR CLARITY.
3. R-NOVA + MATRIX CAN ALSO BE USED IN LIEU OF THE FULLY REINFORCED R-NOVA +FLASHING SYSTEM FOR FLASHING APPLICATIONS. SEE R-NOVA + MATRIX PRODUCT DATA SHEET FOR COVERAGE RATES AND ADDITIONAL INFORMATION.

		310 QUADRAL DRIVE	
		WADSWORTH, OHIO 44281 (330) 334-0066	
TITLE R-NOVA + FLASHING @ CURB			
SCALE NONE	DWN TM	CHK RS	APPROVAL DATE 03/27/12
DRAWING NUMBER R-NOVA+ 002			REV

\*\* USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.