

Roll Width (Y)	Lap Width (Z)	Zone	Pattern	Row Spacing (X)	Fasterners Per Square
	4in	Field	9,9	17.5in	92
39in (1m)		Perimeter	9,9,9,9	8.75in	183
		Corner	9,9,9,9,9	7in	229
	5in	Field	9,9	17in	95
39in (1m)		Perimeter	9,9,9,9	8.5in	189
		Corner	9,9,9,9,9	6.8in	236
	6in	Field	9,9	16.5in	97
39in (1m)		Perimeter	9,9,9,9	8.25in	194
		Corner	9,9,9,9,9	6.6in	243

FASTENING PATTERNS AND ENHANCEMENTS SHOWN ARE FOR SOPREMA WARRANTY PURPOSES ONLY.

PROJECT:



WADSWORTH, OHIO 44281 www.soprema.us Tel:330.334.0066 TITLE: MECHANICALLY ATTACHED BASE PLY,
9" O.C. IN LAP AND ONE ROW BETWEEN LAPS
AT 9" O.C. FASTENING PATTERN

DRAWN BY: SOPREMA TECHNICAL SUPPORT, GGALLOWAY					
NO.:		REVISION:	DATE:		
DATE: 05.10.2014		DRAWING NUMBER:			
SCALE: NTS		US.FP.06.21			