

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : ALSAN® RS Metal Primer

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Single component metal primer

1.3. Details of the supplier of the safety data sheet

Manufacturer:
SOPREMA INC.
310 Quadral Dr.
Wadsworth, OH 44281
Tel: 1-800-356-3521

Distributors:
SOPREMA Canada
1675 Haggerty Street
Drummondville (Quebec) J2C 5P7
Tel: 1-819-478-8163

SOPREMA Canada
44955 Yale Road West
Chilliwack (BC) V2R 4H3
CANADA
Tel: 1-604-793-7100

SOPREMA USA
12251 Seaway Road
Gulfport (Mississippi) 39507
UNITED STATES
Tel: 1-228-701-1900

1.4. Emergency telephone number

Emergency number : CHEMTREC 1-800-434-9300 CANUTEC 1-613-996-6666

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Skin corrosion irritation – Cat 2
Serious eye damage/eye irritation – Cat 2A
Specific target organ toxicity (repeated exposure) (lungs) – Cat 1
Carcinogenicity – Cat 1A

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

May cause cancer
Causes serious eye irritation
Causes skin irritation
Causes damage to organs through prolonged or repeated exposure. (lungs)

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P280 - Wear protective gloves, wear eye or face protection, wear protective clothing.

ALSAN® RS Metal Primer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P308+P313 - If exposed or concerned: Get medical advice/attention
P260 – Do not breathe vapor.
P270 – Do not eat, drink or smoke when using this product.
P264 – Wash hands thoroughly after handling.
P302+P350 – IF ON SKIN: Wash with plenty of soap and water.
P332+P313 If skin irritation occurs: Get medical attention.
P314 – Get medical attention if you feel unwell.
P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
P362+P364 – Take off contaminated clothing and wash it before reuse. Continue rinsing.
P337+P313 – If eye irritation persists: Get medical attention.
P405 – Store locked up.
P501 - Dispose of container in accordance with local, regional or national regulations

2.3. Other hazards

FOR INDUSTRIAL USE ONLY. Adequate ventilation required when sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. DELAYED EFFECTS FROM LONG TERM OVER EXPOSURE. Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure.



WARNING: This product can expose you to chemicals including silica and titanium dioxide which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%
Quartz	(CAS No) 14808-60-7	10- 25
Titanium Dioxide	(CAS No) 13463-67-7	5 - 10
Calcium Carbonate	(CAS No) 1317-65-3	10 - 20
Mica	(CAS No) 12001-26-2	0.1 - 3
Non-hazardous ingredients	N/A	42.0 – 74.9

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
First-aid measures after skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 15 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
First-aid measures after eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 15 minutes. Get medical attention.
First-aid measures after ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

ALSAN® RS Metal Primer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after skin contact : Causes skin irritation. Skin irritation and redness of the skin.
Symptoms/injuries after eye contact : Causes serious eye irritation. Pain or irritation of the eyes. Watering and redness of the eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Note to first responders: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : In a fire or if heated, a pressure increase will occur and the container may burst.
Explosion hazard : No data available.
Reactivity : No data available.
Hazardous thermal decomposition products : Carbon monoxide, phosphorous oxides and metal oxides.

5.3. Advice for firefighters

- Firefighting instructions : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Protection during firefighting : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No smoking.

6.1.1. For non-emergency personnel

- Emergency procedures : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

6.1.2. For emergency responders

- Protective equipment : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up – small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Methods for cleaning up – large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

ALSAN® RS Metal Primer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : No data available.
- Precautions for safe handling : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Hygiene measures : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : No data available.
- Storage conditions : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.
- Incompatible products : No specific data.
- Incompatible materials : No specific data.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Titanium Dioxide (13463-67-7)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ 8 hours. Form total dust
USA ACGIH	ACGIH TLV (TWA) (ppm)	10 mg/m ³ 8 hours.
Calcium Carbonate (1317-65-3)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	TWA: 5 mg/m ³ 8 hours. Form: Respirable fraction TWA: 15 mg/m ³ 8 hours. Form: Total dust
USA ACGIH	ACGIH TLV (TWA) (ppm)	NIOSH REL (United States, 10/2016). TWA: 5 mg/m ³ 10 hours. Form: Respirable fraction TWA: 10 mg/m ³ 10 hours. Form: Total dust
Mica (12001-26-2)		
USA OSHA	OSHA PEL (TWA) Table Z3	TWA: 20 mppcf 8 hours.
USA ACGIH	ACGIH TLV (TWA) (mg/m ³)	TWA: 3 mg/m ³ 8 hours. Form: Respirable fraction
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	TWA: 3 mg/m ³ 10 hours. Form: Respirable fraction
Quartz (14808-60-7)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	TWA: 50 µg/m ³ 8 hours. Form: Respirable dust
USA ACGIH	ACGIH TLV (TWA) (mg/m ³)	TWA: 0.025 mg/m ³ 8 hours. Form: Respirable fraction
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	TWA: 0.05 mg/m ³ 10 hours. Form: respirable dust

8.2. Exposure controls

- Appropriate engineering controls : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

ALSAN® RS Metal Primer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Eye protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.
Skin and body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Other information	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid
Color	: Off-white
Odor	: characteristic
Odor threshold	: No data available
pH	: 9
Relative evaporation rate (butyl acetate=1)	: 0.09
Melting point	: No data available
Freezing point	: No data available
Boiling point	: ≈ 100 °C (212°F)
Flash point	: >93.3 °C (>199.9°F)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: 2.3 kPa (17.5 mm Hg) [at 20°C]
Relative vapor density at 20 °C	: 1 [Air = 1]
Specific Gravity	: 1.34
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: Kinematic (room temperature): >0.205 cm ² /s (>20.5 cSt) Kinematic (40°C (104°F)): >0.205 cm ² /s (>20.5 cSt)
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

VOC content	: 50 g/l
-------------	----------

ALSAN® RS Metal Primer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2. Chemical stability

The product is stable.

10.3. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4. Conditions to avoid

No specific data.

10.5. Incompatible materials

No specific data.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not available

Irritation/Corrosion

Product/ingredient name	Result	Species	Exposure
Titanium Dioxide	Skin – Mild irritant	Human	72 hours 300 micrograms intermittent

Sensitization

Not available

Mutagenicity:

Not available

Carcinogenicity

See table below

Product/ingredient name	OSHA	IARC	NTP
Quartz	-	1	Known to be a human carcinogen
Titanium Dioxide	-	2B	-

Reproductive toxicity:

Not available

Teratogenicity:

Not available

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Calcium carbonate	Category 3	Not applicable	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Crystalline Silica, respirable powder	Category 1	Inhalation	Not determined
Mica	Category 1	Inhalation	lungs

Aspiration hazard:

Not available

Information on likely routes of exposure: Not available

Potential acute health effects:

Eye contact	Causes serious eye irritation.
Inhalation	No known significant effects or critical hazards
Skin contact	Causes skin irritation.
Ingestion	No known significant effects or critical hazards

Symptoms related to the physical, chemical and toxicological characteristics

ALSAN® RS Metal Primer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye contact	pain or irritation, watering, redness
Inhalation	No specific data
Skin contact	Irritation, redness
Ingestion	No specific data

Delayed and immediate effects and also chronic effects from short- and long-term exposure

Short term exposure

Potential immediate effects : Not available
Potential delayed effects : Not available

Long term exposure

Potential immediate effects : Not available
Potential delayed effects : Not available

Potential chronic health effects

Not available

General Causes damage to organs through prolonged or repeated exposure.
Carcinogenicity May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity No known significant effects or critical hazards.
Teratogenicity No known significant effects or critical hazards.
Developmental effects No known significant effects or critical hazards.
Fertility effects No known significant effects or critical hazards

SECTION 12: Ecological information

12.1. Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium Dioxide	Acute LC50 > 1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours

12.2. Persistence and degradability

Not available

12.3. Bioaccumulative potential

Not available

12.4. Mobility in soil

Soil/water partition coefficient (Koc) : Not available

12.5. Other adverse effects

Effect on ozone layer : No known significant effects or critical hazards.

Effect on the global warming : No known significant effects or critical hazards.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

In accordance with DOT not regulated for transport

Additional information

Transport information

	DOT Classification	TDG Classification	IATA (air)	IMDG (sea)
UN number	Not regulated	Not regulated	UN3082	UN3082

ALSAN® RS Metal Primer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

UN proper shipping name	Not regulated	Not regulated	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Zinc Phosphate, Zinc Oxide)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Zinc Phosphate, Zinc Oxide). Marine pollutant (Zinc Phosphate, Zinc Oxide)
Transport hazard class(es)	Not regulated	Not regulated	Not regulated	Not regulated
Packing group	Not regulated	Not regulated	III	III
Environmental Hazards	No	No	Yes	Yes
Additional Information	No	No	This product is not regulated as a dangerous good when transported in sizes of ≤5L or ≤ 5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.	This product is not regulated as a dangerous good when transported in sizes of ≤5L or ≤ 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Emergency schedules_ F-A, S-F

Special precautions for user:

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not available

SECTION 15: Regulatory information

15.1. US regulations

TSCA: TSCA 5(a)2 proposed significant new use rules: 5-Chloro-2-methylisothiazolinone

CALIFORNIA PROP 65:  **WARNING:** This product can expose you to chemicals including silica and titanium dioxide which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

15.2. International regulations

International lists:

Country	Status
Australia inventory (AICS)	Not determined.
China inventory (IECSC)	Not determined.
Japan inventory (ENCS)	Not determined.
Japan inventory (ISHL)	Not determined.
Korea inventory (KECI)	Not determined.
New Zealand Inventory of Chemicals (NZIoC)	Not determined.
Philippines inventory (PICCS)	Not determined.
Taiwan Chemical Substances Inventory (TCSI)	Not determined.
Thailand inventory	Not determined.
Turkey inventory	Not determined.
Vietnam inventory	Not determined.

15.2.2. National regulations

No additional information available

ALSAN® RS Metal Primer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

Revision date : 10/09/19

Other information : None.

Procedure used to derive the classification:

Classification	Justification
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A	Calculation method
CARCINOGENICITY - Category 1A	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (lungs) – Category 1	Calculation method

SDS US (GHS HazCom 2012) - Custom

This SDS contains all the information required by ANSI Z400.1 standard (United States), by regulation 29 CFR Part 1910-1200 of the Hazard Communication Standard of OSHA and is in accordance with DORS/88-66 of WHMIS (Canada).

The best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.