

ALSAN RS PASTE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 11/09/2016

Revision date: 11/09/2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : ALSAN RS PASTE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Rapid-curing PMMA heavy paste for crack filling

1.3. Details of the supplier of the safety data sheet

Manufacturer:
SOPREMA INC.
310 Quadral Dr.
Wadsworth, OH 44281
Tel: 1-800-356-3521

Distributors:
SOPREMA Canada
1675 Haggerty Street
Drummondville (Quebec) J2C 5P7
Tel: 1-819-478-8163

SOPREMA Canada
44955 Yale Road West
Chilliwack (BC) V2R 4H3
CANADA
Tel: 1-604-793-7100

SOPREMA USA
12251 Seaway Road
Gulfport (Mississippi) 39507
UNITED STATES
Tel: 1-228-701-1900

1.4. Emergency telephone number

Emergency number : CHEMTREC 1-800-434-9300 (Acct.# CCN20515). CANUTEC 1-613-996-6666

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 2 H225
Skin Irrit. 2 H315
Skin Sens. 1 H317
Muta. 1B H340
Carc. 1A H350
STOT SE 3 H335

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapor
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H335 - May cause respiratory irritation
H340 - May cause genetic defects (Inhalation)

ALSAN RS PASTE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS-US)	<p>H350 - May cause cancer (Inhalation, however in the manner in which the material is applied, inhalation to quartz is not anticipated).</p> <p>P201 - Obtain special instructions before use P202 - Do not handle until all safety precautions have been read and understood P210 - Keep away from sources of ignition, torches and open flames. - No smoking P233 - Keep container tightly closed P240 - Ground/bond container and receiving equipment P241 - Use explosion-proof electrical equipment P242 - Use only non-sparking tools P243 - Take precautionary measures against static discharge P261 - Avoid breathing vapors P264 - Wash hands thoroughly after handling P271 - Use only outdoors or in a well-ventilated area P272 - Contaminated work clothing must not be allowed out of the workplace P280 - Wear nitrile gloves, appropriate respirator if needed and safety glasses P302+P352 - If on skin: Wash with plenty of water P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P308+P313 - If exposed or concerned: Get medical advice/attention P312 - Call a poison center if you feel unwell P321 - Specific treatment (see a doctor) P332+P313 - If skin irritation occurs: Get medical advice/attention P333+P313 - If skin irritation or rash occurs: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse P363 - Wash contaminated clothing before reuse P370+P378 - In case of fire: Use foam, dry extinguishing powder, water spray, carbon dioxide (CO2), sand to extinguish P403+P233 - Store in a well-ventilated place. Keep container tightly closed P403+P235 - Store in a well-ventilated place. Keep cool P405 - Store locked up P501 - Dispose of container in accordance with local, regional or national regulations</p>
-----------------------------------	--

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Quartz	(CAS No) 14808-60-7	10 - 30	Carc. 1A, H350
methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropanoate	(CAS No) 80-62-6	7 - 20	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335
2-ethylhexyl acrylate	(CAS No) 103-11-7	7 - 20	Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335
Stoddard solvent	(CAS No) 8052-41-3	0.03 - 0.48	Muta. 1B, H340 Carc. 1B, H350
Naphtha (petroleum), hydrodesulfurized heavy	(CAS No) 64742-82-1	0.03 - 0.48	Muta. 1B, H340 Carc. 1B, H350

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

ALSAN RS PASTE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Get medical advice/attention. Specific treatment (see a doctor). If skin irritation or rash occurs: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May cause genetic defects.
- Symptoms/injuries after inhalation : May cause an allergic skin reaction. May cause cancer by inhalation (however, in the manner in which this material is applied, inhalation exposure to quartz is not anticipated). May cause respiratory irritation.
- Symptoms/injuries after skin contact : Causes skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapor.
- Explosion hazard : May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No naked lights. No smoking. Use only non-sparking tools. Avoid breathing vapors. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so. Use only outdoors or in a well-ventilated area.

ALSAN RS PASTE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene measures : Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical equipment.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Heat sources, Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking, Keep away from ignition sources. Keep in fireproof place. Keep container tightly closed.

Incompatible products : Strong bases. Strong acids.

Storage temperature : 0°C - 25 °C or 32°F - 77 °F

Incompatible materials : Sources of ignition. Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate (80-62-6)		
USA ACGIH	ACGIH TWA (ppm)	50 ppm
USA ACGIH	ACGIH STEL (ppm)	100 ppm
USA ACGIH	Remark (ACGIH)	URT & eye irr; body weight eff; DSEN; RSEN; A4
USA OSHA	OSHA PEL (TWA) (mg/m ³)	410 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
Stoddard solvent (8052-41-3)		
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA ACGIH	Remark (ACGIH)	Eye, skin, & kidney dam;
USA OSHA	OSHA PEL (TWA) (mg/m ³)	2900 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm
Quartz (14808-60-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 R
USA OSHA	Remark (US OSHA)	(3) See Table Z-3.

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear nitrile or butyl rubber gloves.

Eye protection : Chemical goggles or safety glasses.

Skin and body protection : Wear suitable protective clothing including long sleeve shirt and long pants.

Respiratory protection : Wear appropriate mask if needed.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Paste.

Color : Gray

Odor : characteristic

Odor threshold : No data available

pH : No data available

Relative evaporation rate (butyl acetate=1) : No data available

Melting point : No data available

Freezing point : No data available

Boiling point : ≈ 101 °C

ALSAN RS PASTE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flash point	: $\approx 2\text{ }^{\circ}\text{C}$ MMA closed cup
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Specific Gravity	: No data available
Density	: $\approx 1.34\text{ g/cm}^3$
Percent Solids	: $\approx 72\%$
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: $\approx 4500\text{ mPa}\cdot\text{s}$
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

VOC content : < 10 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Naphtha (petroleum), hydrodesulfurized heavy (64742-82-1)	
LD50 oral rat	> 5000 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	> 7.63 mg/l/4h (Rat; Experimental value)
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: May cause genetic defects (Inhalation).
Carcinogenicity	: May cause cancer (Inhalation, however, in the manner in which the material is applied, inhalation exposure to quartz is not anticipated).

methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate (80-62-6)	
IARC group	3 - Not classifiable
2-ethylhexyl acrylate (103-11-7)	
IARC group	3 - Not classifiable

ALSAN RS PASTE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause an allergic skin reaction. May cause cancer by inhalation (however, in the manner in which the material is applied, inhalation exposure to quartz is not anticipated). May cause respiratory irritation.
Symptoms/injuries after skin contact	: Causes skin irritation.

SECTION 12: Ecological information

12.1. Toxicity

Naphtha (petroleum), hydrodesulfurized heavy (64742-82-1)	
LC50 fish 1	8.2 mg/l (LL50; EPA 660/3 - 75/009; 96 h; Pimephales promelas; Semi-static system; Fresh water; Experimental value)
EC50 Daphnia 1	4.5 mg/l (EL50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 1	3.7 mg/l (EL50; OECD 201: Alga, Growth Inhibition Test; 96 h; Selenastrum capricornutum; Static system; Fresh water; Experimental value)

12.2. Persistence and degradability

ALSAN RS PASTE	
Persistence and degradability	Not established.
methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate (80-62-6)	
Persistence and degradability	Not established.
2-ethylhexyl acrylate (103-11-7)	
Persistence and degradability	Not established.
Stoddard solvent (8052-41-3)	
Persistence and degradability	Not established.
Naphtha (petroleum), hydrodesulfurized heavy (64742-82-1)	
Persistence and degradability	Readily biodegradable in water. Highly mobile in soil. Adsorbs into the soil. Not established.
Quartz (14808-60-7)	
Persistence and degradability	Biodegradability: not applicable. Not established.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

12.3. Bioaccumulative potential

ALSAN RS PASTE	
Bioaccumulative potential	Not established.
methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate (80-62-6)	
Bioaccumulative potential	Not established.
2-ethylhexyl acrylate (103-11-7)	
Bioaccumulative potential	Not established.
Stoddard solvent (8052-41-3)	
Bioaccumulative potential	Not established.
Naphtha (petroleum), hydrodesulfurized heavy (64742-82-1)	
BCF fish 1	10-2500,BCF; EPIWIN BCF (v 2.15)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500). Not established.

ALSAN RS PASTE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Quartz (14808-60-7)	
Log Pow	Not applicable
Bioaccumulative potential	No bioaccumulation data available. Not established.

12.4. Mobility in soil

Naphtha (petroleum), hydrodesulfurized heavy (64742-82-1)	
Log Koc	log Koc,SRC PCKOCWIN v1.66; 1.783-2.36; Calculated value

12.5. Other adverse effects

- Effect on ozone layer : No additional information available.
- Effect on the global warming : No known ecological damage caused by this product.
- Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of container in accordance with local, regional or national regulations.
- Additional information : Handle empty containers with care because residual vapors are flammable.
- Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

- In accordance with DOT
- Transport document description : UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base), 3, II
- UN-No.(DOT) : 1263
- DOT NA no. : UN1263
- DOT Proper Shipping Name : Paint
including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base
- Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Hazard labels (DOT) : 3 - Flammable liquid



- Packing group (DOT) : II - Medium Danger
- DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons)
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F)
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP
- DOT Packaging Exceptions (49 CFR 173.xxx) : 150
- DOT Packaging Non Bulk (49 CFR 173.xxx) : 173
- DOT Packaging Bulk (49 CFR 173.xxx) : 242
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

ALSAN RS PASTE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded

Additional information

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

ADR

Transport document description :

Transport by sea

UN-No. (IMDG) : 1263

Proper Shipping Name (IMDG) : PAINT

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : II - substances presenting medium danger

Air transport

UN-No.(IATA) : 1263

Proper Shipping Name (IATA) : PAINT

Class (IATA) : 3 - Flammable Liquids

Packing group (IATA) : II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

ALSAN RS PASTE

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate (80-62-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on United States SARA Section 313

CERCLA RQ	1000 lb
-----------	---------

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

15.2.2. National regulations

No additional information available

15.3. US State regulations

ALSAN RS PASTE

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

ALSAN RS PASTE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate (80-62-6)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	No	No	No	

2-ethylhexyl acrylate (103-11-7)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	No	No	No	

Stoddard solvent (8052-41-3)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	No	No	No	

Naphtha (petroleum), hydrodesulfurized heavy (64742-82-1)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	No	No	No	

Quartz (14808-60-7)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	No	No	No	

methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate (80-62-6)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				

2-ethylhexyl acrylate (103-11-7)				
U.S. - New Jersey - Right to Know Hazardous Substance List				

Stoddard solvent (8052-41-3)				
U.S. - New Jersey - Right to Know Hazardous Substance List				

Quartz (14808-60-7)				
U.S. - New Jersey - Right to Know Hazardous Substance List				

SECTION 16: Other information

Revision date : 11/09/2016

Other information : None.

Full text of H-phrases::


H225	Highly flammable liquid and vapor
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H335	May cause respiratory irritation
H340	May cause genetic defects
H350	May cause cancer

ALSAN RS PASTE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard	: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA fire hazard	: 3 - Liquids and solids that can be ignited under almost all ambient conditions.
NFPA reactivity	: 2 - Normally unstable and readily undergo violent decomposition but do not detonate. Also: may react violently with water or may form potentially explosive mixtures with water.



HMIS III Rating

Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard
Physical	: 2 Moderate Hazard
Personal Protection	: G

SDS US (GHS HazCom 2012) - Custom

This SDS contains all the information required by ANSI Z400.1 standard (United States), by regulation 29 CFR Part 1910-1200 of the Hazard Communication Standard of OSHA and is in accordance with DORS/88-66 of WHMIS (Canada).

The best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.