

ALSAN TRAFIK PU 215

BASE COAT ACCELERATOR

ALSAN Trafik PU 215
ACCELERATOR

PRODUCT #
00513157

PRODUCT DATA SHEET

DESCRIPTION & FEATURES

ALSAN Trafik PU 215 is a liquid accelerator that is added to ALSAN Trafik PU 215 polyurethane elastomeric base membrane. This accelerator shortens the cure time of the ALSAN Trafik PU 215 in cold weather.

STORAGE

Always store sealed containers in a cool, well ventilated and dry location. Do not store in direct sunlight or temperatures below 60F or above 95F. Approximate shelf life is six months from date of manufacture when properly stored, sealed and unmixed.

APPLICATION AND MIXING

ALSAN Trafik PU 215 should be thoroughly mixed prior to adding the ALSAN Trafik PU 215 Accelerator. ALSAN Trafik PU 215 should be mixed using a jiffy blade mixer at slow speed for at least 2-3 minutes. Add the ALSAN Trafik PU 215 Accelerator to the entire 5 gallon pail and thoroughly mix prior to application to ensure a consistent homogeneous material from top to bottom. The ALSAN Trafik PU 215 Accelerator will reduce the cure time of ALSAN Trafik PU 215.

QUICK FACTS

CONTAINER
(ounce)

1.5



www.soprema.us
310 Quadral Drive, Wadsworth, Ohio 44281
Toll Free: (800) 356-3521 | Tel: (330) 334-0066

ALSAN Trafik PU 215

BASE COAT ACCELERATOR

TECHNICAL INFORMATION & TESTING

PHYSICAL PROPERTIES		
PROPERTY	VALUE	TEST METHOD
Specific Gravity	1.008 +/- 0.05	-
Viscosity @ 75°F, cps	100 +/- 50	-
Solids by weight, %	100	ASTM D2369
Solids by volume, %	100	ASTM D2697
VOC (volatile organic compounds), g/L	0	ASTM D2369-81
Color	Pink or Blue	-