

ALSAN TRAFIK PU 215

BASE COAT ACCELERATOR

ALSAN Trafik PU 215
ACCELERATOR

PRODUCT DATA SHEET

DESCRIPTION & FEATURES

ALSAN Trafik PU 215 Base Coat accelerator is a one-component coating catalyst that can be used with ALSAN Trafik PU 215 Base Coat to reduce cure times of the coating for projects with expedited scheduling requirements.

STORAGE

Always store sealed containers in a cool, well ventilated and dry location. Do not store in direct sunlight or temperatures below 60°F (16°C) or above 95°F (35°C). Approximate shelf life is six months from date of manufacture when properly stored, sealed and unmixed.

APPLICATION AND MIXING

ALSAN Trafik PU 215 Base Coat should be thoroughly stirred prior to adding ALSAN Trafik PU 215 Base Coat accelerator. ALSAN Trafik PU 215 Base Coat is mixed with water and the accelerator using a jiffy blade mixer at low speed until the water and accelerator disappear, typically 2-3 minutes. 0 to 3 vials of ALSAN Trafik PU 215 Base Coat accelerator can be added to the 5 gallon pail of ALSAN Trafik PU 215 Base Coat to control cure times in the field.

QUICK FACTS

CONTAINER
(ounce)

1.5



www.soprema.us
310 Quadral Drive, Wadsworth, Ohio 44281
Toll Free: (800) 356-3521 | Tel: (330) 334-0066

ALSAN TRAFIK PU 215

BASE COAT ACCELERATOR

TECHNICAL INFORMATION & TESTING

PHYSICAL PROPERTIES		
PROPERTY	VALUE	TEST METHOD
Specific Gravity	1.008	-
Viscosity @ 75°F, cps	100	-
Solids by weight, %	100	ASTM D2369
Solids by volume, %	100	ASTM D2697
VOC (volatile organic compounds), g/L	0	ASTM D2369-81
Color	Pink	-

*Data is represented by average values unless otherwise noted.