

ELASTOCOL®

500

ELASTOCOL® 500
PRODUCT # D35735

PRODUCT DATA SHEET

DESCRIPTION & FEATURES

ELASTOCOL 500 is an asphalt based primer for use in approved multi-ply membrane and flashing assemblies. ELASTOCOL 500 is composed of a proprietary blend of asphalt, solvents and additives used to increase adhesion when using heat welding, cold adhesive or hot asphalt application methods.

STORAGE

Store in pail and maintain in an upright position to prevent damage. Store in a clean dry location and cover as necessary to protect pails from environmental damage such as extreme cold, heat, or moisture. Monitor varying environmental conditions during storage, handling and application of ELASTOCOL 500.

APPLICATION

Mix prior to application. ELASTOCOL 500 is applied to the approved area via brush, roller or spray equipment. ELASTOCOL 500 is applied at a rate of 0.35 to 0.6 gallon per 100 square feet over non porous substrate. Refer to the SOPREMA SBS Roofing Manual for additional application guidelines.



QUICK FACTS

ASTM STANDARD	CONTAINER (gal)	COVERAGE RATE (gal/100ft ²)
D41 TYPE 1	5.0 (18.9 L)	0.35-0.6 (0.15-0.25 L/m ²)

PRODUCT INFORMATION

Description	Proprietary blend of asphalt and solvents
Installation	Spray, brush or roller
Packaging	5 gallon (18.9 L) pail

TESTING & APPROVALS



FLORIDA BUILDING CODE

MIAMI-DADE COUNTY
APPROVED



SOPREMA®

www.soprema.us
310 Quadral Drive, Wadsworth, Ohio 44281
Toll Free: (800) 356-3521 | Tel: (330) 334-0066

PD10136 - REV. 029018