

# ELASTOCOL®

## STICK ZERO

ELASTOCOL® STICK ZERO  
PRODUCT # D37700

## PRODUCT DATA SHEET

### DESCRIPTION & FEATURES

ELASTOCOL Stick Zero is a zero VOC polymer based primer for use in approved multi-ply membrane and flashing assemblies. ELASTOCOL Stick Zero is composed of a proprietary blend of polymers, solvents and additives used to increase adhesion when using self-adhered SBS membranes. ELASTOCOL Stick Zero may be applied to gypsum, masonry, metal, wood and SOPREMA's mineral aggregate surfaced membranes.

### STORAGE

Store in pail and maintain in an upright position to prevent damage. Store in a clean dry location and cover as necessary to protect pails from environmental damage such as extreme cold, heat, or moisture. Monitor varying environmental conditions during storage, handling and application of ELASTOCOL Stick Zero.

### APPLICATION

Mix prior to application. ELASTOCOL Stick Zero is applied to the approved area via brush, roller or spray equipment. ELASTOCOL Stick Zero is applied at a rate of 0.7 to 1 gallon per 100 square feet over non porous substrates. Refer to the SOPREMA SBS Roofing Manual for additional application guidelines.



### QUICK FACTS

CONTAINER (gal)	COVERAGE RATE (gal/100ft <sup>2</sup> )
5.0 (18.9 L)	0.7-1.0 (0.3-0.4 L/m <sup>2</sup> )

### PRODUCT INFORMATION

Description	Propreitary blend of synethetic polymers, solvents and resins
Installation	Brush or roller
Packaging	5 gallon (18.9 L) pail

## TESTING & APPROVALS



FLORIDA BUILDING CODE



**SOPREMA®**

[www.soprema.us](http://www.soprema.us)  
310 Quadral Drive, Wadsworth, Ohio 44281  
Toll Free: (800) 356-3521 | Tel: (330) 334-0066

PD10133 - REV. 026416