

ELASTOCOL® 350

ELASTOCOL® 350
PRODUCT # D35240

PRODUCT DATA SHEET

DESCRIPTION & FEATURES

ELASTOCOL 350 is a zero VOC, water based primer for use in approved multi-ply membrane and flashing assemblies. ELASTOCOL 350 is a proprietary polymer emulsion zero VOC primer used to increase adhesion when using heat welding, cold adhesive or hot asphalt application methods.

STORAGE

Store in pail and maintain in an upright position to prevent damage. Store in a clean dry location and cover as necessary to protect pails from environmental damage such as extreme cold, heat, or moisture. Monitor varying environmental conditions during storage, handling and application of ELASTOCOL 350.

APPLICATION

Mix prior to application. ELASTOCOL 350 is applied to the approved area via brush, roller or spray equipment. ELASTOCOL 350 is applied at a rate of 0.5 to 0.8 gallons per 100 square feet over non porous substrates. Refer to the SOPREMA SBS Roofing Manual for additional application guidelines.



QUICK FACTS

CONTAINER (gal)	COVERAGE RATE (gal/100ft ²)
5.0 (18.9 L)	0.5-0.8 (0.2-0.3 L/m ²)

PRODUCT INFORMATION

Description	Proprietary polymer emulsion primer
Installation	Spray, brush or roller
Packaging	5 gallon (18.9 L) pail

TESTING & APPROVALS

FLORIDA BUILDING CODE



SOPREMA®

www.soprema.us
310 Quadral Drive, Wadsworth, Ohio 44281
Toll Free: (800) 356-3521 | Tel: (330) 334-0066

PD10135 - REV. 026416