

SOPRANATURE™

SEAM TAPE

SOPRANATURE™
SEAM TAPE
PRODUCT #
W808

PRODUCT DATA SHEET

DESCRIPTION & FEATURES

SOPRANATURE Seam Tape is a high performance, low-residue adhesive seam tape with low water vapor permeance. SOPRANATURE Seam Tape is specially designed to seal and protect seams from moisture. SOPRANATURE Seam Tape is available in 4 inch wide rolls, providing a greater area of adhesion.

STORAGE & HANDLING

Store product in a clean dry location and cover as necessary to protect from environmental damage such as extreme cold, heat, or moisture.

APPLICATION

Unroll and lap SOPRANATURE Seam Tape over joints and seams in the SOPRANATURE Root Barrier. To allow for maximum adhesion, ensure that the application area is free of dust, dirt and moisture.

QUICK FACTS

ROLL SIZE (in/ft)	THICKNESS (mils)	ADHESIVE THICKNESS (mil)
4" x 180' (96 mm x 55 mm)	7.5 (0.190 mm)	3.0 (0.076 mm)



www.soprema.us
310 Quadral Drive, Wadsworth, Ohio 44281
Toll Free: (800) 356-3521 | Tel: (330) 334-0066

TECHNICAL INFORMATION & TESTING

PHYSICAL PROPERTIES		
PROPERTY	VALUE	ASTM
Material	Polyethylene	-
Tensile Strength (new material), lbs/in (N/25 mm)	24 (105)	D1000
Water Vapor Permeance, perms (perms metric)	< 0.001 (< 0.0007)	E96
Operating Temperature Range, °F (°C)	32° to 160° (0° to 70°)	-
Tape Color	White	-
Elongation %	70	D1000