

ANTIROCK®

EMULSION PRIMER

ANTIROCK®
EMULSION PRIMER
PRODUCT #
D36750 (5 gal)
D36751 (53 gal)

PRODUCT DATA SHEET

DESCRIPTION & FEATURES

ANTIROCK Emulsion Primer is a bituminous emulsion (stabilized blend of bitumen and water without solvent). It is used to prime concrete and metal surfaces on civil engineering structures in order to improve the adhesion of ANTIROCK waterproofing membranes.

STORAGE

Store in a pail and maintain in an upright position to prevent damage. Store in a clean, dry location and cover as necessary to protect pails from environmental damage such as freezing temperatures, heat, or moisture. Monitor varying environmental conditions during storage, handling and application of ANTIROCK Emulsion Primer. Approximate shelf life is 12 months from date of manufacture when properly sealed and unopened containers, in a cool and ventilated area.

APPLICATION

Mix prior to application. ANTIROCK Emulsion Primer can be applied to the approved area via brush, roller or spray equipment. ANTIROCK Emulsion Primer is applied at a rate of 150-250 square feet per gallon over non porous substrates. Refer to the SOPREMA ANTIROCK specifications for additional application guidelines.

APPLICATION



BRUSH



ROLLER



SPRAY

QUICK FACTS

CONTAINER (gal)		COVERAGE RATE (ft ² /gal)
5 (18.9 L)	53 (200 L)	150-250 (3.7-6.1 m ² /L)



SOPREMA®

www.soprema.us
310 Quadral Drive, Wadsworth, Ohio 44281
Toll Free: (800) 356-3521 | Tel: (330) 334-0066

PD10374 - REV. 005619