

ALSAN® COATING SIL WALKWAY GRANULES

ALSAN® COATING SIL
WALKWAY GRANULES
PRODUCT #
L-SILWWG

PRODUCT DATA SHEET

DESCRIPTION & FEATURES

ALSAN COATING SIL Walkway Granules are quartz granules, designed to provide slip & impact resistance to designated areas of a roof surface. ALSAN Coating SIL Walkway Granules have superior UV resistance and will retain their color as they age.

APPLICATION

ALSAN COATING SIL Walkway Granules are immediately applied into the wet ALSAN COATING SIL Walkway Grade, at a rate of 40 lbs./sq. for walkway areas and 60 lbs./sq. for high traffic areas. See ALSAN COATING SIL Walkway Grade PDS for application rates of the coating.

PHYSICAL PROPERTIES

PROPERTY		TEST METHOD
Hardness	6.5 - 7.0	Moh's Hardness Scale
Bulk Density, Lbs. / Cu. Ft.	90 - 100	ASTM C29/C29M-97
Specific Gravity	2.65	ASTM C128-01E1
Silica Sand	97.5%	N/A
Resin	2.0%	N/A
Colorants	0.5%	N/A
Packaging, Gallons	2	N/A



SOPREMA®

www.soprema.us
310 Quadral Drive, Wadsworth, Ohio 44281
Toll Free: (800) 356-3521 | Tel: (330) 334-0066

PDS10275 - REV. 025318