

PRODUCT DATA SHEET

DESCRIPTION & FEATURES

SENTINEL Walkway Pad protects roof membranes from damage caused by necessary foot traffic or accidental tool drops. This product is compatible with SENTINEL PVC roof membranes and can be applied to new or existing roofs using standard hot air welding equipment.

STORAGE

Store rolls on end and maintain in an upright position to prevent damage. Store rolls in a clean, dry location and cover as necessary to protect rolls from environmental damage such as extreme cold, heat or moisture. Monitor varying environmental conditions during storage, handling and application.

APPLICATION

Remove any loose debris and clean PVC roof membrane, then allow to dry prior to application of walkway. Roll out and cut desired length up to 10' (3 m) and allow to relax while placing into the desired position. Install SENTINEL Walkway Pad with a continuous weld around the perimeter. Refer to SOPREMA's specifications and installation instructions for additional application guidelines.

QUICK FACTS

WIDTH (in)	LENGTH (ft)	ROLL WEIGHT (lbs)	COLOR
30 (76.2 cm)	50 (15.2 m)	80 (36 kg)	Light gray

PHYSICAL PROPERTIES

PROPERTY	MD	TEST METHOD
Thickness, in (mm)	0.156 (4)	ASTM D412
Tear resistance, lbf/in (kN/m)	200 (35)	ASTM D624
Elongation, %	100	ASTM D412
Dimensional stability, %	0.25 (max change)	ASTM D1204
Accelerated weathering	Pass @ 5,000 hours	ASTM G155

* Data is represented by average values, unless noted otherwise.

