

SOPRAMASTIC® ALU

SOPRAMASTIC® ALU
PRODUCT # D35652

PRODUCT DATA SHEET

DESCRIPTION & FEATURES

SOPRAMASTIC ALU is a modified bitumen mastic for use in approved multi-ply membrane and flashing assemblies. SOPRAMASTIC ALU is composed of a proprietary formulation of elastomeric modified bitumen and solvents. SOPRAMASTIC ALU is aluminum hued for application to membrane edge and perimeter metal.

STORAGE

Store in box and maintain in an upright position to prevent damage. Store in a clean dry location and cover as necessary to protect box from environmental damage such as extreme cold, heat, or moisture. Monitor varying environmental conditions during storage, handling and application of SOPRAMASTIC ALU.

APPLICATION

SOPRAMASTIC ALU is applied to the approved area via a caulking gun. Refer to the SOPREMA SBS Roofing Manual for additional application guidelines.



QUICK FACTS

QUANTITY (oz)

16.9
(0.5 kg)

PRODUCT INFORMATION

Description	Sealant compound
Installation	Caulking gun
Packaging	16.9 oz (0.5 kg) plastic tube
Application rate	Coverage varies according to size of bead, temperature at application and technique used by installer



www.soprema.us
310 Quadral Drive, Wadsworth, Ohio 44281
Toll Free: (800) 356-3521 | Tel: (330) 334-0066

PD10110 - REV. 0003916