


NOTES:

1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPROVED DETAILS AND ALSAN FLASHING (AF) APPLICATION AND COVERAGE DIRECTIONS.
2. ALSAN FLASHING 20 WET MILS COVERAGE RATE IS 1.25 GALS/100FT. ALL COVERAGE RATES ARE APPROXIMATE, THEORETICAL AND DO NOT ACCOUNT FOR WASTE, SPILLAGE, IRREGULAR SURFACES AND APPLICATION TECHNIQUES THAT CAN ALSO VARY WITH INSTALLER. RATES MAY ALSO VARY DEPENDING UPON MATERIAL AND AMBIENT TEMPERATURE(S), SURFACE FINISH AND POROSITY OF THE SUBSTRATE.
3. FLASHING MAY BE TERMINATED AT GRADE
4. A BASE LAYER OF COLPHENE FLAM 180 MAY BE USED

 SOPREMA <small>WATERPROOFING DIVISION</small>		310 QUADRAL DRIVE WADSWORTH, OHIO 44281 (330) 334-0066		
		TITLE ANTIROCK UPSTAND DETAIL (BRIDGES, PARKING DECKS)		
SCALE	NONE	DWN TM	CHK JP	APPROVAL DATE 06/30/10
DRAWING NUMBER				REV
ANTO2				0

** USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.