

METAL DRIP EDGE-ABRADE & CLEAN FLANGE
W/SOPREMA ALSAN RS MEMBRANE CLEANER &
SET IN BED OF ACCEPTABLE SEALER.

SOPREMA ALSAN RS MEMBRANE FLASHING-EXTEND
FULL WIDTH OF FLANGE & 4" (10cm) MIN. ONTO
PREPARED & PRIMED SUBSTRATE.

FASTENERS 4" (10cm) O.C., STAGGERED 1".

SOPREMA ALSAN RS FIELD MEMBRANE

2" MIN (5cm) 1/4" HEM


4" (10cm)

PREPARE, LEVEL & PATCH SUBSTRATE W/ ALSAN RS PASTE
OR ACCEPTABLE PATCHING MORTAR PRIOR TO APPLICATION
OF SOPREMA ALSAN RS PRIMER & MEMBRANE (TYP.)

CONTINUOUS CLEAT, FASTENED 6" (15cm) (MAX.)

NOTES:

1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS
AND APPROVED DETAILS.

		310 QUADRAL DRIVE	
		WADSWORTH, OHIO 44281	
		(330) 334-0066	
TITLE			
DRIP EDGE FLASHING			
SCALE	DWN	CHK	APPROVAL DATE
NONE	DMT	MT	5/30/07
DRAWING NUMBER			REV
E-2-RS			0

** USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL.
PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.