

CUT-IN REGLET 1" MIN. DEEP, APPLY APPROVED CAULKING AS REQUIRED

SOPREMA ALSAN RS MEMBRANE FLASHING—EXTEND 10" (25cm) MIN. HORIZONTALLY ONTO MODIFIED BITUMEN/BUR MEMBRANE.

ACCEPTABLE PATCHING MATERIALS TO PROVIDE SMOOTH TRANSITION BETWEEN SUBSTRATE & BUR.

EXISTING MODIFIED BITUMEN CAP SHEET OR BUR MEMBRANE PREPARED CLEANED & PRIMED AS REQUIRED.

1" MIN.


2" MIN. (5cm)

10" (25cm) MIN.

PREPARE, LEVEL & PATCH SUBSTRATE W/ ALSAN RS PASTE OR ACCEPTABLE PATCHING MORTAR PRIOR TO APPLICATION OF SOPREMA ALSAN RS PRIMER & MEMBRANE (TYP.)

NOTES:

1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.

		310 QUADRAL DRIVE	
		WADSWORTH, OHIO 44281 (330) 334-0066	
TITLE WATERPROOFING MEMBRANE TIE-IN TO MODIFIED BITUMEN\BUR MEMBRANE			
SCALE	DWN	CHK	APPROVAL DATE
NONE	DMT	MT	7/28/09
DRAWING NUMBER			REV
M-4b-RS			0

\*\* USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.