

IRREGULAR PENETRATION POWER TOOL CLEAN METAL SURFACE TO BE FLASHED PER SSPC-SP3.

SURFACE PREP MAX. 1/8" BEYOND SOPREMA ALSAN RS FLASHING COVERED W/ SOPREMA ALSAN RS RESIN.

SOPREMA ALSAN RS MEMBRANE SKIRT WRAPPED AROUND METAL PENETRATION W/2" MIN. OVERLAP AT ALL JOINTS.

1/8" TYP.

6" (15cm) MIN.

4" (10cm) MIN.

4" (10cm) MIN.

4" (10cm) MIN.


2" (5cm) MIN.

SOPREMA ALSAN RS FIELD MEMBRANE

SOPREMA ALSAN RS MEMBRANE COLLAR CUT SNUG FIT AROUND PENETRATION SAME SIZE AS BASE ANGLE SHAPE.

NOTES:

1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.

		310 QUADRAL DRIVE	
		WADSWORTH, OHIO 44281	
		(330) 334-0066	
TITLE			
ANGLE SUPPORT FLASHING			
SCALE	DWN	CHK	APPROVAL DATE
NONE	DMT	MT	5/30/07
DRAWING NUMBER			REV
P-4a-RS			0

** USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.