

IRREGULAR PENETRATION POWER TOOL CLEAN METAL SURFACE TO BE FLASHED PER SSPC-SP3.

SURFACE PREP MAX. 1/8" BEYOND SOPREMA ALSAN RS FLASHING COVERED W/ SOPREMA ALSAN RS RESIN.

SOPREMA ALSAN RS MEMBRANE SKIRT WRAPPED AROUND METAL PENETRATION W/2" MIN. OVERLAP AT ALL JOINTS.

1/8" TYP.

4" (10cm) MIN.

SOPREMA ALSAN RS FIELD MEMBRANE

4" (10cm) MIN.

6" (15cm) MIN.


SOPREMA ALSAN RS MEMBRANE COLLAR CUT SNUG FIT AROUND SAME SIZE AS I-BEAM PENETRATION SHAPE.

4" (10cm) MIN.

2" (5cm) MIN.

NOTES:

1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.

		310 QUADRAL DRIVE WADSWORTH, OHIO 44281 (330) 334-0066	
		TITLE C-CHANNEL SUPPORT FLASHING	
SCALE	DWN DMT	CHK MT	APPROVAL DATE 5/30/07
DRAWING NUMBER P-4c-RS			REV 0

** USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.