

Roll Width (Y)	Lap Width (Z)	Zone	Pattern	Row Spacing (X)	Fasteners Per Square
36in (0.9m)	2in	Field	7.5,7.5,7.5	11.33in	169
		Perimeter	8.5,8.5,8.5,8.5,8.5,8.5	5.67in	299
		Corner	5.5,5.5,5.5,5.5,5.5	5.67in	462
		Field	7.5,7.5,7.5	11in	175
36in (0.9m)	3in	Perimeter	8.5,8.5,8.5,8.5,8.5,8.5	5.5in	308
		Corner	5.5,5.5,5.5,5.5,5.5	5.5in	476
36in (0.9m)	4in	Field	7.5,7.5,7.5	10.67in	180
		Perimeter	8.5,8.5,8.5,8.5,8.5,8.5	5.33in	318
		Corner	5.5,5.5,5.5,5.5,5.5	5.33in	491
		Field	7.5,7.5,7.5	12in	160
39in (1m)	3in	Perimeter	8.5,8.5,8.5,8.5,8.5,8.5	6in	282
		Corner	5.5,5.5,5.5,5.5,5.5	6in	436
39in (1m)	4in	Field	7.5,7.5,7.5	11.67in	165
		Perimeter	8.5,8.5,8.5,8.5,8.5,8.5	5.83in	290
		Corner	5.5.5.5.5.5.5.5.5.5.5	5.83in	449

FASTENING PATTERNS AND ENHANCEMENTS SHOWN ARE FOR SOPREMA WARRANTY PURPOSES ONLY.

PRC

TITL



www.soprema.us Tel:330.334.0066

ROJECT:		DRAWN BY: SOPREMA TECHNICAL SUPPORT, GGALLOWAY			
		REVISION:		DATE:	
TLE:					
7.5, 7.5, 7.5 BASE SHEET FASTENING PATTERN	DATE: 03.31.2014		DRAWING NUMBER:		
PATIERN	SCALE: N	TS	US.FP.01.04		