

Roll Width (Y)	Lap Width (Z)	Zone	Pattern	Row Spacing (X)	Fasteners Per Square
	2in	Field	8,8,8	11.33in	159
36in (0.9m)		Perimeter	7.5,7.5,7.5,7.5	6.8in	282
		Corner	6,6,6,6,6,6	5.67in	424
	3in	Field	8,8,8	11in	164
36in (0.9m)		Perimeter	7.5,7.5,7.5,7.5	6.6in	291
		Corner	6,6,6,6,6,6	5.5in	436
	4in	Field	8,8,8	10.67in	169
36in (0.9m)		Perimeter	7.5,7.5,7.5,7.5	6.4in	300
		Corner	6,6,6,6,6,6	5.33in	450
	3in	Field	8,8,8	12in	150
39in (1m)		Perimeter	7.5,7.5,7.5,7.5	7.2in	267
		Corner	6,6,6,6,6,6	6in	400
	4in	Field	8,8,8	11.67in	154
39in (1m)		Perimeter	7.5,7.5,7.5,7.5	7in	274
		Corner	6,6,6,6,6,6	5.83in	411

FASTENING PATTERNS AND ENHANCEMENTS SHOWN ARE FOR SOPREMA WARRANTY PURPOSES ONLY.

PROJECT:

TITLE:



WADSWORTH, OHIO 44281 www.soprema.us Tel:330.334.0066 8,8,8 BASE SHEET FASTENING PATTERN

DRAWN BY: SOPREMA TECHNICAL SUPPORT, GGALLOWAY					
NO.:		REVISION:	DATE:		
DATE: 03.31.2014		DRAWING NUMBER: US.FP.01.06			
SCALE: NTS					