


Roll Width (Y)	Lap Width (Z)	Zone	Pattern	Row Spacing (X)	Fasteners Per Square
39in (1m)	4in	Field	8,8	17.5in	103
		Perimeter	8,8,8,8	8.75in	206
		Corner	8,8,8,8,8	7in	258
39in (1m)	5in	Field	8,8	17in	106
		Perimeter	8,8,8,8	8.5in	212
		Corner	8,8,8,8,8	6.8in	265
39in (1m)	6in	Field	8,8	16.5in	110
		Perimeter	8,8,8,8	8.25in	219
		Corner	8,8,8,8,8	6.6in	273

FASTENING PATTERNS AND ENHANCEMENTS SHOWN ARE FOR SOPREMA WARRANTY PURPOSES ONLY.

 <p>US CORPORATE ADDRESS 310 QUADRAL DRIVE WADSWORTH, OHIO 44281 www.soprema.us Tel:330.334.0066</p>	PROJECT:	DRAWN BY: SOPREMA TECHNICAL SUPPORT, GGALLOWAY		
	TITLE: MECHANICALLY ATTACHED BASE PLY, 8" O.C. IN LAP AND ONE ROW BETWEEN LAPS AT 8" O.C. FASTENING PATTERN	NO.:	REVISION:	DATE:
		DATE: 05.10.2014	DRAWING NUMBER: <b>US.FP.06.22</b>	
		SCALE: NTS		

USAGE OF THIS DETAIL IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAILS. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.